

ICS monitoring

SMART SPECTRUM MONITORING SOLUTION BASED ON SERVICE-ORIENTED PLATFORM

Monitoring of emissions, spectrum usage assessment, control of licensed emissions, multi sensors.

- ▶ **ONE SINGLE SYSTEM GATHERING-FLEXIBILITY AND SCALABILITY**
- ▶ **MULTITASK MEASUREMENTS – BIG DATA PROCESSING**
- ▶ **AUTOMATIC POST-PROCESSING REAL TIME OPERATION**

ICS monitoring is a specific spectrum product from the ATDI spectrum management system range: performs tasks in accordance with Radio Regulations, checks the conformity of the conditions of frequency allocations/frequency usage and channel occupancy. ICS monitoring analyses cases of interferences, detects unauthorized broadcasts emissions and offers the flexibility of the SDRN Control structure.

MAIN FEATURES:


- Full and real time integration with licensed equipment database
- Automated storage of electromagnetic situation measurements and data analysis
- Establishment of spectrum reference situation based both on measurement results and propagation
- Modelling
- Real time spectrum analysis without interruption of measurements already launched
- Background mode measurements do not require human intervention
- Integrated GIS (map layers and terrain data)
- Spectrum Occupancy measurements
- Detection of unauthorised emissions
- Licensed transmitters data collection and storage
- Comparison of spectrum emissions with spectrum masks of authorized transmitters
- Comparison of spectrum emissions with reference spectrum masks
- Bandwidth measurements
- Frequency band scanning
- Localization of unauthorised emissions
- Hybrid localization (TDOA / AOA / POA / RSSI)
- HOMING (Machine learning algorithm – HTZ required)




SDRN Control & Modular Design

TWO POSSIBLE ARCHITECTURE MODES:

▶ SDRN CLUSTERED MODE ARCHITECTURE



▶ SDRN SINGLE MODE ARCHITECTURE




SERVER MODULES:

- **SDRN Controls (SDRN CS)**
 - application server
 - centralized data processing
 - support for work of measurements management services
 - analysis of monitoring results
- **SDRN Control server aggregation (SDRN CSA)**
 - software module for load balancing point into cluster
- **SDRN Control server infocenter (SDRN CSI)**
 - software module for high performance data access between different sources within cluster
- **SDRN Control server calculation (SDRN CSC)**
 - software module for high performance massive computing by propagation models

END POINT MODULES:



- **SDRN ControlIU (SDRN CU)**
 - software module for management of spectrum monitoring hardware through user interface
- **SDRN ControlIA (SDRN CA)**
 - software module for management of spectrum monitoring hardware in automated mode
- **SDRN Control API (SDRN API)**
 - software module for interface with third party software
- **SDRN Control plug-in for ICS manager**

Physical Architecture



SOA Architecture

TYPICAL LOGICAL STRUCTURE FOR SERVER-BASED SOLUTIONS



KEY LAYERS:

• PUBLIC SERVICES

- SA selection of components for the WCF/REST services

• APP OPERATIONS

- SA set of components for implementing for user-defined functions

• CORE

- an application service for managing components hosting and publishing DI (*Dependency Injection*) Containers

• COMMAND CORE

- contains instrumental service to manage application servers

• SERVICE MODULES

- components of subject-matter logic which can be distributed

• THE COMMUNICATION BUS

- an intermediate layer providing connectivity between all service modules and the client

ICS monitoring controls spectrum analyzers, measuring receivers, modulation analyzers, cellular communication network analyzers, remote and devices.

**DISCOVER MORE
ON OUR PRODUCT
AND SERVICES**

contact@atdi-group.com
11 boulevard Malesherbes,
75008 Paris, France